

DECLARATION OF PERFORMANCE
No. S – DECOPLASTER DÉCOR STANDARD

1. Unique identification code of the product-type: **DECOPLASTER DÉCOR STANDARD**
2. Intended use/es: **Designed Coloured rendering mortar (CR /CS II / W_c2), for internal and external use.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies: **No tasks for the notified body**

6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
Reaction to Fire:	Class A1	EN 998-1:2016
Adhesion:	≥ 0.6 N/mm ² FP:B	
Capillary water absorption:	W _c 2	
Water vapour permeability coefficient (μ):	μ ≤ 12	
Thermal conductivity λ_{10, dry}:	0.72 W/m*K (tabulated mean value, P=50%)	
Release of dangerous substances:	See SDS	

Appropriate Technical Documentation: included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Decision 96/603/EU and following amendments.

Organic material < 1% by mass.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 12/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

	
11	
EAGLE S.A. / AETOS A.E. INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" Industrial park of Prosotsani, 66200 Drama, Greece	
DoP No. S – DECOPLASTER DÉCOR STANDARD EN 998-1	
DECOPLASTER DÉCOR STANDARD Designed Coloured rendering mortar (CR /CS II / W _c 2), for internal and external use.	
Reaction to Fire:	Class A1
Adhesion:	≥ 0.6 N/mm ² FP:B
Capillary water absorption:	W _c 2
Water vapour permeability coefficient (μ):	μ ≤ 12
Thermal conductivity λ_{10, dry}:	0.72 W/m*K (tabulated mean value, P=50%)
Release of dangerous substances:	See SDS