

DECLARATION OF PERFORMANCE

No. PS – EASYROLL

1. Unique identification code of the product-type: **EASYROLL**
2. Intended use/es: **Factory-made, water-based organic render/plaster, for internal and external use on walls, ceiling, columns and partitions.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 15824:2017**
Notified body/ies: **No tasks for the notified body**
6. Declared performance/s:

| Essential characteristics | Performance | Harmonised Technical Specification |
|---|--|------------------------------------|
| Reaction to Fire: | NPD | EN 15824:2017 |
| Adhesion: | ≥ 0.5 MPa | |
| Water absorption: | W ₃ | |
| Water vapour permeability: | V ₂ | |
| Thermal conductivity $\lambda_{10, dry}$: | 0.62 W/m*K (tabulated mean value, P=50%) | |
| Release of dangerous substances: | See SDS | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 12/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

| | |
|--|--|
|  | |
| 13 | |
| EAGLE S.A. / AETOS A.E. INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" Industrial park of Prosotsani, 66200 Drama, Greece | |
| DoP No.: PS – EASYROLL EN 15824 | |
| EASYROLL Factory-made, water-based organic render/plaster, for internal and external use on walls, ceiling, columns and partitions. | |
| Reaction to Fire: | NPD |
| Adhesion: | ≥ 0.5 MPa |
| Water absorption: | W ₃ |
| Water vapour permeability: | V ₂ |
| Thermal conductivity λ_{10, dry}: | 0.62 W/m*K (tabulated mean value, P=50%) |
| Release of dangerous substances: | See SDS |