

DECLARATION OF PERFORMANCE

No. THER - FL100ST BIOPAN

1. Unique identification code of the product-type: **FL 100ST BIOPANOPLY**
2. Intended use/es: **Designed general purpose rendering/plastering mortar (GP/CS IV) for internal and external use on walls, ceilings, columns and partitions.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.**
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies: **No tasks for the notified body**

6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
Reaction to Fire:	A2 -S1, d0	EN 998-1:2016
Adhesion:	$\geq 0.8 \text{ N/mm}^2$ - FP:B	
Capillary water absorption:	$W_c 2$	
Water vapour permeability coefficient (μ):	$\mu \leq 15$	
Thermal conductivity $\lambda_{10, \text{dry}}$:	0.52 W/m*K (Tabulated mean value (P=50%))	
Release of dangerous substances:	See SDS	

Appropriate Technical Documentation: included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Delegated Regulation (EU) 2017/1228 dated 20.03.2017 and following amendments.

Maximum organic content ≤ 2.5 % in weight.

Maximum mass per unit area ≤ 6.0 kg/m²

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 12/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.



08

EAGLE S.A. / AETOS A.E.
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
Industrial park of Prosotsani, 66200 Drama, Greece

DoP No.: THER - FL100ST BIOPAN

EN 998-1

FL 100ST BIOPANOPLY

Designed general purpose rendering/plastering mortar (GP/CS IV) for internal and external use on walls, ceilings, columns and partitions.

Reaction to Fire:	A2 -S1, d0
Adhesion:	$\geq 0.8 \text{ N/mm}^2$ - FP:B
Capillary water absorption:	$W_c 2$
Water vapour permeability coefficient (μ):	$\mu \leq 15$
Thermal conductivity $\lambda_{10, \text{dry}}$:	0.52 W/m*K (Tabulated mean value (P=50%))
Release of dangerous substances:	See SDS