

DECLARATION OF PERFORMANCE
No. STE – MARMOFLEX HYBRID

1. Unique identification code of the product-type: **MARMOFLEX HYBRID**
2. Intended use/es: **Coating product for intended use in concrete surface protection, in uses with low performance subject to reaction to fire regulations.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 1504-2:2004**
Notified body/ies: **No tasks for the notified body**
6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
Reaction to Fire:	Class F	EN 1504-2:2004
Permeability to water vapour:	Class I (Sd < 5m)	
Capillary absorption and permeability to water:	< 0.1 kgr/m ² ·h ^{0,5}	
Adhesion strength by pull-off test:	≥ 1.5 N/mm ²	
Permeability to CO₂:	Sd > 50m	
Release of dangerous substances:	Comply with 5.3	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 16/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

	
18	
EAGLE S.A. / AETOS A.E. INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" Industrial park of Prosotsani, 66200 Drama, Greece	
DoP No.: STE – MARMOFLEX HYBRID EN 1504-2	
MARMOFLEX HYBRID Coating product for intended use in concrete surface protection, in uses with low performance subject to reaction to fire regulations.	
Reaction to Fire:	Class F
Permeability to water vapour:	Class I (Sd < 5m)
Capillary absorption and permeability to water:	< 0.1 kgr/m ² ·h ^{0,5}
Adhesion strength by pull-off test:	≥ 1.5 N/mm ²
Permeability to CO₂:	Sd > 50m
Release of dangerous substances:	Comply with 5.3