

**DECLARATION OF PERFORMANCE**  
**No. PS – SILICONE PLASTER DECOR**

1. Unique identification code of the product-type: **SILICONE PLASTER DECOR**
2. Intended use/es: **Factory-made, water-based organic render/plaster, for internal and external use on walls, ceiling, columns and partitions.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**  
**INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY**  
**BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”**  
**INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.**
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 15824:2017**  
Notified body/ies: **No tasks for the notified body**

6. Declared performance/s:

| Essential characteristics                                   | Performance                              | Harmonised Technical Specification |
|---|--|------------------------------------|
| <b>Reaction to Fire:</b>                                    | Class B - s2, d0                         | EN 15824:2017                      |
| <b>Adhesion:</b>  | ≥ 0.5 MPa                                |                                    |
| <b>Water absorption:</b>                                    | W <sub>2</sub>                           |                                    |
| <b>Water vapour permeability:</b>                           | V <sub>2</sub>                           |                                    |
| <b>Thermal conductivity <math>\lambda_{10, dry}</math>:</b> | 0.52 W/m*K (tabulated mean value, P=50%) |                                    |
| <b>Release of dangerous substances:</b>                     | See SDS                                  |                                    |

Appropriate Technical Documentation: included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Delegated Regulation (EU) 2017/1228 dated 20.03.2017 and following amendments.

Maximum organic content  $\leq 9.0$  % in weight.

Maximum mass per unit area  $\leq 4.0$  kg/m<sup>2</sup>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Athanasios Lazaridis  
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 12/05/23

**REACH information:** the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

|  |  |
|--|--|
|   |  |
| <b>15</b>  |  |
| <b>EAGLE S.A. / AETOS A.E.</b><br><b>INDUSTRIAL, COMMERCIAL &amp; TRANSPORT COMPANY</b><br><b>BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"</b><br><b>Industrial park of Prosotsani, 66200 Drama, Greece</b> |  |
| <b>DoP No.: PS – SILICONE PLASTER DECOR</b><br><b>EN 15824</b>   |  |
| <b>SILICONE PLASTER DECOR</b><br>Factory-made, water-based organic render/plaster, for internal and external use on walls, ceiling, columns and partitions.  |  |
| <b>Reaction to Fire:</b>   | Class B - s2, d0                         |
| <b>Adhesion:</b>   | ≥ 0.5 MPa                                |
| <b>Water absorption:</b>   | W <sub>2</sub>                           |
| <b>Water vapour permeability:</b>  | V <sub>2</sub>                           |
| <b>Thermal conductivity λ<sub>10, dry</sub>:</b>   | 0.52 W/m*K (tabulated mean value, P=50%) |
| <b>Release of dangerous substances:</b>  | See SDS                                  |