

DECLARATION OF PERFORMANCE No. PS – SILICONE PLASTER GRAFIATO

1. Unique identification code of the product-type: SILICONE PLASTER GRAFIATO

2. Intended use/es: Factory-made, water-based organic render/plaster, for internal and external use on walls, ceiling, columns and partitions.

- 3. Manufacturer: EAGLE S.A. / AETOS A.E. INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
- 4. System/s of AVCP: System 4
- 5. Harmonised standard: EN 15824:2017 Notified body/ies: No tasks for the notified body

Essential characteristics	Performance	Harmonised Technical Specification
Reaction to Fire:	Class B - s2, d0	
Adhesion:	≥ 0.5 MPa	_
Water absorption:	W2	EN 15824:2017
Water vapour permeability:	V2	
Thermal conductivity $\lambda_{10, dry}$:	0.52 W/m*K (tabulated mean value, P=50%)	
Release of dangerous substances:	See SDS	







Appropriate Technical Documentation: included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Delegated Regulation (EU) 2017/1228 dated 20.03.2017 and following amendments.

Maximum organic content ≤ 9.0 % in weight.

Maximum mass per unit area $\leq 4.0 \text{ kg/m}^2$

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis Q.C. / R&D Manager

At: Prosotsani, Drama, Greece

on 12/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.





CE

15

EAGLE S.A. / AETOS A.E.

INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" Industrial park of Prosotsani, 66200 Drama, Greece

DoP No.: PS - SILICONE PLASTER GRAFIATO

EN 15824

SILICONE PLASTER GRAFIATO

Factory-made, water-based organic render/plaster, for internal and external use on walls, ceiling, columns and partitions.

Reaction to Fire:	Class B - s2, d0
Adhesion:	≥ 0.5 MPa
Water absorption:	W ₂
Water vapour permeability:	V ₂
Thermal conductivity $\lambda_{10, dry}$:	0.52 W/m*K (tabulated mean value, P=50%)
Release of dangerous substances:	See SDS

