

DECLARATION OF PERFORMANCE
No. THER - BIOPANOPLY ACRYL

1. Unique identification code of the product-type: **BIOPANOPLY ACRYL**
2. Intended use/es: **Factory-made, water-based organic render/plaster, for internal and external use on walls, ceiling, columns and partitions.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 15824:2017**
Notified body/ies: **No tasks for the notified body**

6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
Reaction to Fire:	NPD	EN 15824:2017
Adhesion:	> 0.3 MPa	
Water absorption:	W ₂	
Water vapour permeability:	V ₂	
Thermal conductivity $\lambda_{10, dry}$:	0.40 W/m*K (tabulated mean value, P=50%)	
Release of dangerous substances:	See SDS	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 01/01/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

	
15	
EAGLE S.A. / AETOS A.E. INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" Industrial park of Prosotsani, 66200 Drama, Greece	
DoP No.: THER - BIOPANOPLY ACRYL EN 15824	
BIOPANOPLY ACRYL Factory-made, water-based organic render/plaster, for internal and external use on walls, ceiling, columns and partitions.	
Reaction to Fire:	NPD
Adhesion:	> 0.3 MPa
Water absorption:	W ₂
Water vapour permeability:	V ₂
Thermal conductivity $\lambda_{10, dry}$:	0.40 W/m*K (tabulated mean value, P=50%)
Release of dangerous substances:	See SDS