

## DECLARATION OF PERFORMANCE

No. STE – MARMOFLEX PU W

1. Unique identification code of the product-type: **MARMOFLEX PU W**
2. Intended use/es: **Coating product for intended use in concrete surface protection, in uses with low performance subject to reaction to fire regulations.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**  
**INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY**  
**BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”**  
**INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.**
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 1504-2:2004**  
Notified body/ies: **No tasks for the notified body**
6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
<b>Reaction to Fire:</b>	Class F	EN 1504-2:2004
<b>Permeability to water vapour:</b>	Class I (Sd < 5m)	
<b>Capillary absorption and permeability to water:</b>	< 0.1 kgr/m <sup>2</sup> ·h <sup>0,5</sup>	
<b>Adhesion strength by pull-off test:</b>	≥ 1.5 N/mm <sup>2</sup>	
<b>Permeability to CO<sub>2</sub>:</b>	Sd > 50m	
<b>Release of dangerous substances:</b>	Comply with 5.3	

7. Appropriate Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Athanasios Lazaridis  
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 16/05/23

**REACH information:** the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

	
<b>18</b>	
<b>EAGLE S.A. / AETOS A.E.</b> <b>INDUSTRIAL, COMMERCIAL &amp; TRANSPORT COMPANY</b> <b>BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"</b> <b>Industrial park of Prosotsani, 66200 Drama, Greece</b>	
DoP No.: <b>STE – MARMOFLEX PU W</b> <b>EN 1504-2</b>	
<b>MARMOFLEX PU W</b> Coating product for intended use in concrete surface protection, in uses with low performance subject to reaction to fire regulations.	
<b>Reaction to Fire:</b>  <b>Permeability to water vapour:</b>  <b>Capillary absorption and permeability to water:</b>  <b>Adhesion strength by pull-off test:</b>  <b>Permeability to CO<sub>2</sub>:</b>  <b>Release of dangerous substances:</b>	Class F  Class I (Sd < 5m)  < 0.1 kgr/m <sup>2</sup> ·h <sup>0,5</sup>  ≥ 1.5 N/mm <sup>2</sup>  Sd > 50m  Comply with 5.3