

DECLARATION OF PERFORMANCE
No. STE – HY DROCEM

1. Unique identification code of the product-type: **HY DROCEM**
2. Intended use/es: **Cementitious liquid-applied, water impermeable product CM 01P, for all external installations and swimming pools beneath ceramic tiling, (bonded with a C2 adhesive in accordance with EN 12004).**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 3 (for water tightness)**
System 4
5. Harmonised standard: **EN 14891:2017**
Notified body/ies: **No 2860**

6. Declared performance/s:

| Essential characteristics | Performance | Harmonised Technical Specification |
|--|--|------------------------------------|
| Initial tensile adhesion strength: | ≥ 0.5 N/mm ² | EN 14891:2017 |
| Waterproofing: | No penetration | |
| Crack bridging ability: <ul style="list-style-type: none"> • under standard conditions (+23°C) • at low temperature (-5° C) | ≥ 0,75 mm ≥ 0,75 mm | |
| Durability for tensile adhesion strength: <ul style="list-style-type: none"> • after water contact: • after heat ageing: • after freeze-thaw cycles : • after contact with lime water: | ≥ 0,5 N/mm ² ≥ 0,5 N/mm ² ≥ 0,5 N/mm ² ≥ 0,5 N/mm ² | |
| Tensile adhesion strength after contact with chlorinated water: | ≥ 0,5 N/mm ² | |
| Release of dangerous substances: | See SDS | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 01/11/22

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

| | |
|--|--|
|  2860 | |
| 22 | |
| EAGLE S.A. / AETOS A.E. INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" Industrial park of Prosotsani, 66200 Drama, Greece | |
| DoP No.: STE – HY DROCEM EN 14891 | |
| HY DROCEM Cementitious liquid-applied, water impermeable product CM 01P, for all external installations and swimming pools beneath ceramic tiling, (bonded with a C2 adhesive in accordance with EN 12004). | |
| Initial tensile adhesion strength: | ≥ 0.5 N/mm ² |
| Waterproofing: | No penetration |
| Crack bridging ability: <ul style="list-style-type: none"> • under standard conditions (+23°C) • at low temperature (-5° C) | ≥ 0,75 mm ≥ 0,75 mm |
| Durability for tensile adhesion strength: <ul style="list-style-type: none"> • after water contact: • after heat ageing: • after freeze-thaw cycles : • after contact with lime water: | ≥ 0,5 N/mm ² ≥ 0,5 N/mm ² ≥ 0,5 N/mm ² ≥ 0,5 N/mm ² |
| Tensile adhesion strength after contact with chlorinated water: | ≥ 0,5 N/mm ² |
| Release of dangerous substances: | See SDS |