

DECLARATION OF PERFORMANCE

No. S - TE 75

1. Unique identification code of the product-type: **TE 75 FAST**
2. Intended use/es: **Designed general purpose rendering/plastering mortar (GP / CS III) for external and internal use on walls, ceilings, columns and partitions.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies: **No tasks for the notified body**
6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
Reaction to Fire:	Class A1	EN 998-1:2016
Adhesion:	1,6 N/mm ² FP:B	
Capillary water absorption:	W _c 1	
Water vapour permeability coefficient (μ):	μ ≤ 12	
Thermal conductivity λ_{10, dry}:	0.57 W/m*K (tabulated mean value, P=50%)	
Release of dangerous substances:	See SDS	

Appropriate Technical Documentation: included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Decision 96/603/EU and following amendments.

Organic material < 1% by mass.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 15/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.



20

EAGLE S.A. / AETOS A.E.

INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
Industrial park of Prosotsani, 66200 Drama, Greece

DoP No.: S - TE 75

EN 998-1

TE 75 FAST

Designed general purpose rendering/plastering mortar (GP / CS III) for external and internal use on walls, ceilings, columns and partitions.

Reaction to Fire:

Class A1

Adhesion:

1,6 N/mm² FP:B

Capillary water absorption:

W_c 1

Water vapour permeability coefficient (μ):

μ ≤ 12

Thermal conductivity λ_{10, dry}:

0.57 W/m*K (tabulated mean value, P=50%)

Release of dangerous substances:

See SDS