

DECLARATION OF PERFORMANCE

No. S – MONOPLASTER PRO

1. Unique identification code of the product-type: **MONOPLASTER PRO**
2. Intended use/es: **Designed one coat rendering/plastering mortar (OC/CS II) for external and internal use on walls, ceilings and columns.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies: **No tasks for the notified body**

6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
Reaction to Fire:	Class A1	EN 998-1:2016
Adhesion after weathering cycles:	$\geq 0.4 \text{ N/mm}^2$ FP:B	
Water permeability on relevant substrates after weathering cycles:	$\leq 1 \text{ ml/cm}^2$ after 48 h	
Water vapour permeability coefficient (μ):	$\mu \leq 12$	
Thermal conductivity $\lambda_{10, \text{dry, mat}}$:	0.65 W/m*K (tabulated mean value, P=50%)	
Release of dangerous substances:	See SDS	

Appropriate Technical Documentation: included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Decision 96/603/EU and following amendments.

Organic material < 1% by mass.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 31/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

	
23	
EAGLE S.A. / AETOS A.E. INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" Industrial park of Prosotsani, 66200 Drama, Greece	
DoP No.: S – MONOPLASTER PRO EN 998-1:2016	
MONOPLASTER PRO Designed one coat rendering/plastering mortar (OC/CS II) for external and internal use on walls, ceilings and columns.	
Reaction to Fire: Adhesion after weathering cycles: Water permeability on relevant substrates after weathering cycles: Water vapour permeability coefficient (μ): Thermal conductivity $\lambda_{10, dry, mat}$: Release of dangerous substances:	Class A1 $\geq 0.4 \text{ N/mm}^2$ FP:B $\leq 1 \text{ ml/cm}^2$ after 48 h $\mu \leq 12$ 0.65 W/m*K (tabulated mean value, P=50%) See SDS