

## DECLARATION OF PERFORMANCE

No. KP – ULTRAFLEX PRO

1. Unique identification code of the product-type: **ULTRAFLEX PRO**
2. Intended use/es: **Improved, cementitious adhesive (C2TES2), for internal and external tiling on floors and walls.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**  
**INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY**  
**BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”**  
**INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.**
4. System/s of AVCP: **System 3**  
**System 4 (Reaction to fire)**
5. Harmonised standard: **EN 12004-1:2017**  
Notified body/ies: **NB 1871**
6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
<b>Reaction to Fire:</b>	Class E	EN 12004-1:2017
<b>Bond strength:</b>	expressed as: initial tensile adhesion strength $\geq 1.0 \text{ N/mm}^2$	
<b>Durability against:</b>	expressed as:	
<b>climate/heat ageing action:</b>	- tensile adhesion strength after heat ageing $\geq 1.0 \text{ N/mm}^2$	
<b>water/humidity action:</b>	- tensile adhesion strength after water immersion $\geq 1.0 \text{ N/mm}^2$	
<b>freeze-thaw cycles:</b>	- tensile adhesion strength after freeze-thaw cycles $\geq 1.0 \text{ N/mm}^2$	
<b>Release of dangerous substances:</b>	See SDS	

Appropriate Technical Documentation: included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Decision 2010/81/EU.

Organic material < 20% by weight

Maximum layer thickness 20 mm

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis  
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 07/11/24

**REACH information:** the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

 <b>1871</b>	
<b>24</b>	
<b>EAGLE S.A. / AETOS A.E.</b> <b>INDUSTRIAL, COMMERCIAL &amp; TRANSPORT COMPANY</b> <b>BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”</b> <b>Industrial park of Prosotsani, 66200 Drama, Greece</b>	
<b>DoP No.: KP – ULTRAFLEX PRO</b> <b>EN 12004</b>	
<b>ULTRAFLEX PRO</b> Improved, cementitious adhesive (C2TES2), for internal and external tiling on floors and walls.	
Reaction to Fire:	Class E
Bond strength:	expressed as: initial tensile adhesion strength $\geq 1.0 \text{ N/mm}^2$
Durability against:  climate/heat ageing action: water/humidity action: freeze-thaw cycles:	expressed as:  - tensile adhesion strength after heat ageing $\geq 1.0 \text{ N/mm}^2$ - tensile adhesion strength after water immersion $\geq 1.0 \text{ N/mm}^2$ - tensile adhesion strength after freeze-thaw cycles $\geq 1.0 \text{ N/mm}^2$
Release of dangerous substances:	See SDS